★★
STANDARD

Masonry saw TBE400

Cutting depth up to 125 mm

Swivelling saw head enables 45° mitre cuts

Folding feet, transport wheels and carrying handles ensure total manoeuvrability at the location of use

Angle stop provided for cuts of 30° to 90°

The TBE400 table saw offers an uncompromising price-performance ratio as well as high flexibility through numerous settings and application options. A sturdy saw table with anti-slip support guarantees clean cuts. The swivelling saw head allows mitre cuts to be made with ease. Transport wheels and folding table feet facilitate transport and position at the location of use.

System & accessories

Technical data

Saw blade	
Max. cutting depth	125 mm
Max. saw blade Ø	400 mm
Cutting length	600 mm
Saw blade speed	2 800 rpm
Saw blade arbour Ø	25.4 mm

Drive	
Drive / motor	Electric
Power	2.2 kW
Voltage / standard frequency	230 V / 50 Hz
Motor cooling	Air cooling
Saw blade drive	Direct

Design
Continuously variable cutting depth
Angle cutting function (angle stop)
Mitre cutting function (swivelling saw head)
Cap cutting function
Water tank made of powder-coated steel
Easy to replace electric water pump
Folding feet and transport handles

Dimensions & weight	
Length	1 210 mm
Width	655 mm
Height	1 285 mm
Weight	86 kg

System & accessories

Masonry saw TBE400	
10998400	Masonry saw TBE400 / 230 V